

Saws

High safety
and long service life



The saws are extremely pleasant to work with because the rubber-coated handle reduces vibrations and protects your hands from the cold. Furthermore, the stop bracket makes sure that your working results turn out perfectly.

Body saw



- Safety lever prevents unintentional start-up
- Stop bracket ensures reliable saw guidance and extends the useful life of saw blades
- Non-slip rubber handle reduces vibrations and prevents cold hands

- No dust dispersion due to exhaust air hose

Scope of delivery: D322321: 1 saw blade;
D322320: in Systainer with 2x5 saw blades



Type	Art. no.	Air requirements (l/min)	Working pressure (bar)	Stroke rate (min ⁻¹)	Stroke length (mm)	Cutting thickness (mm)	Weight (kg)
KS 9A-SYS	D322320	200	6,3	9300	9	1,2	0,9
KS 9A	D322321	200	6,3	9300	9	1,2	0,9

Saw blades



- Bi-metal version
- Quantity in pack: 5

Type	Art. no.	For metal plate thickness (mm)	Length of cutting blade (mm)	Pitch (mm)
SGB-Bimet 0,3-0,8/5	B322520	0,3 – 0,8	50	0,8
SGB-Bimet 0,8-1,2/5	B322521	0,8 – 1,2	50	1,0

Special cutter



The special cutter
for flexible operation



This special cutter is particularly handy and user-friendly, primarily due to the low weight and compact design of the machine. The safety lever prevents the user from switching on the machine unintentionally and reduces the risk of injury as a result.

Special cutter



- Handy, lightweight tool
- Oscillating drive with 20,000 oscillations
- Suitable for continuous use
- 19 mm hexagon tool holder
- No dust dispersion due to exhaust air hose
- Safety lever prevents unintentional start-up
- Compatible with standard grinding discs, diamond wheels, scrapers and cutters

Scope of delivery: in Systainer; One straight, one straight-stepped and one curved-stepped knife



Type	Art. no.	Air requirements (l/min)	Working pressure (bar)	Vibrations (min ⁻¹)	Weight (kg)
SPA-SYS	D322669	280	6,3	20.000	1,0

Accessories for special cutter



- Knife set (1 straight-flat, straight-offset, bent-offset knife respectively)

Type	Art. no.
MR-Set-HW-SPA	B322284

Riveting tongs

Tidies up even during work



These riveting tongs have a special storage container that catches the rivets while you are working. A selection of various rivet guides makes them suitable for different rivets – the air requirements of the tool are low as well.

Blind rivet gun



- Different rivet guides allow the use of all standard rivet types
- Rivet pins collect in container, reducing your workload
- Can be used on building sites in combination with small compressors because of low air requirement

- For rivet sizes 2.4 – 4.8 mm

Scope of delivery: in Systainer; Various rivet holders, 4 x 10 riveting bolts



Type	Art. no.	Air requirements (l/stroke)	Working pressure (bar)	Riveting (Ø mm)	Weight (kg)
NZ-SYS	D322311	1,1	6,3	2,4 – 4,8	1,7

Grease guns

Fast working progress
without great effort



The long hose on these grease guns can reach into the most difficult areas with ease – the extremely versatile guns can take 400 g cartridges or loose grease and are the only guns available with two venting valves for easier ventilation.

Grease gun

Common features

- With 1:40 pressure ratio. 6 bar input pressure corresponds to 240 bar pressure at the hydraulic nipple
- Quick and easy working progress with two convenient venting valves
- For standard 400 g cartridges or poured grease
- 4-claw retainer system for perfect grip of the grease nipple
- With robust metal casing



FP-M

- Manual grease gun
- A shot of grease is produced every time the trigger is pressed
- With 200 mm connection hose



FP-A

- Automatic grease gun
- Grease is delivered when the trigger lever is pressed and stops when the trigger is released
- The 800 mm long connecting hose enables you to reach awkward spots
- Can be used with grease NLGI, stages 1-3

Type	Art. no.	Air requirements (l/stroke)	Working pressure (bar)	Weight (kg)
FP-M	D040025	0,6	2-10	1,5
FP-A	D040026	0,6	2-10	1,5

Oil extracting device



Quiet
and durable



This oil extracting device has two suction probes that enable you to work more quickly and an extra-large nozzle that allows you to empty the vessel without using tools. Suitable for all kinds of application.

Oil extraction device



- The plug adapter for the suction probes ensure rapid probe changes without requiring tools
 - 2 suction probes attached via connector sleeves for rapid working
 - Impact-resistant plastic casing for a long service life
 - Quiet due to exhaust air silencer
 - The large 20 cm nozzle allows for rapid vessel drainage without requiring tools
 - Wide base for extra stability
 - Locking lever for smooth continuous operation
- Scope of delivery:** With 3 probes (7 and 10 mm in dia., length 1 m)



Type	Art. no.	Air requirements (l/min)	Working pressure (bar)	Tank vol. (l)	Weight (kg)
OBG	D040152	160	6,3	5,5	1,7

Needle descalers

Specially robust
all-metal enclosure



The needle descalers in a solid metal housing have an impressively long service life and are fitted with extremely durable needles made from special steel.

Needle descaler



Straight needle descaler



- Robust metal casing for a long service life
- Special steel needles with an extended useful life, needle length 145 mm, dia. 3 mm
- Guide bush easy to remove for rapid needle replacement, no tools required

Scope of delivery: in Systainer




Type	Art. no.	Air requirements (l/min)	Working pressure (bar)	Stamping number (min ⁻¹)	Number of needles	Weight (kg)
NP-AT 12 SYS	D322415	120	6,3	4000	12	1,2

Gun needle descaler




- Robust metal casing for a long service life
- Special steel needles with an extended useful life, needle length 145 mm, dia. 3 mm
- Depth adjustment of needle guide bush for perfect adaptation to changing working conditions
- Gun grip for ergonomic handling

Scope of delivery: in Systainer



Type	Art. no.	Air requirements (l/min)	Working pressure (bar)	Stamping number (min ⁻¹)	Number of needles	Weight (kg)
NP-AT 28 SYS	D322414	220	6,3	4500	28	3,5

Spare needles



Type	Art. no.	Contents
AT 12	B322279	Set with 12 pieces for AT 12
AT 28	B322281	Set with 28 pieces for AT 28