

## Stapler




- For attaching wall panelling, tongue and groove boards, profiled boards and furniture back boards as well as manufacturing boxes and fences, suitable for exhibition construction and interior fittings
- Compact design, effortless work for long periods due to low weight
- Contact release for rapid working progress
- With depth regulator for adjusting the insertion depth
- Non-slip rubber handle reduces vibrations and prevents cold hands
- Rotatable exhaust air guide
- For type 90 staples, length 13-40 mm

**Scope of delivery:** in Systainer; Protective goggles; 2000 type 90 staples, length 30 mm



Type	Art. no.	Air requirements (l/impact)	Working pressure (bar)	Magazine capacity	Weight (kg)
KLG 90-40 SYS	D200098	0,8	5 – 8	100	1,1

## Staples, type 90



- C = chisel point
- NK = galvanised
- H = resinated
- V2A: stainless steel
- Price for bulk quantities on request

Type	Art. no.	Back width (mm)	Wire gauge (mm)	Length (mm)	Packaging unit (piece(s))	Bulk buying (piece(s))
KL 90/15 CNKH/2000	C420022	5,7	1,25x1,0	15	2000	20000
KL 90/20 CNKH/2000	C420024	5,7	1,25x1,0	20	2000	20000
KL 90/25 CNKH/2000	C420027	5,7	1,25x1,0	25	2000	20000
KL 90/28 CNKH/5000	C420029	5,7	1,25x1,0	28	5000	25000
KL 90/30 CNKH/2000	C420030	5,7	1,25x1,0	30	2000	20000
KL 90/30 CV2AH/5000	C421030	5,7	1,25x1,0	30	5000	25000
KL 90/35 CNKH/2000	C420034	5,7	1,25x1,0	35	2000	20000
KL 90/40 CNKH/2000	C420035	5,7	1,25x1,0	40	2000	20000

## Stapler



- For attaching plasterboard, OSBs and chip board as well as manufacturing pallets, boxes, crates, shuttering, etc.
- With depth regulator for adjusting the insertion depth
- Selection between single release and contact release for rapid working progress
- Front panel easy to open without tools in the event of problems
- Non-slip rubber handle reduces vibrations and prevents cold hands
- Rotatable exhaust air guide
- For type 114 staples, up to 64 mm
- TIP: Set the working pressure or insertion depth so that the staple only sinks in slightly to prevent tearing away when working with plasterboards

**Scope of delivery:** Protective goggles



Type	Art. no.	Air requirements (l/impact)	Working pressure (bar)	Magazine capacity	Weight (kg)
KLG 114-65	D200094	1,3	5 – 8	130	2,5

## Staples, type 114



- Corresponds to standard DIN 18182-D40-D63
- NK = galvanised
- C = chisel point
- H = resinated

Type	Art. no.	Back width (mm)	Wire gauge (mm)	Length (mm)	Packaging unit (piece(s))
KL 114/30 CNKH/20000	C430021	10,8	1,6x1,4	30	20000
KL 114/35 CNKH/10000	C430022	10,8	1,6x1,4	35	10000
KL 114/40 CNKH/10000	C430023	10,8	1,6x1,4	40	10000
KL 114/45 CNKH/10000	C430024	10,8	1,6x1,4	45	10000
KL 114/50 CNKH/10000	C430025	10,8	1,6x1,4	50	10000
KL 114/65 CNKH/10000	C430026	10,8	1,6x1,4	65	10000

## Combination nailer



- For staples (invisible joints in the jaws of the groove on tongue and groove boards) and pan-head nails (edges of wood panelling, decorative or profiled strips and skirting board)
- With depth regulator for adjusting the insertion depth
- Safe to use with contact fuse
- Non-slip rubber handle reduces vibrations and prevents cold hands
- Rubber cap for the contact safety catch prevents damage to sensitive wood
- The rubber contact points with anti-slip function protect sensitive surfaces
- Front panel easy to open without tools in the event of problems
- For type SN pan-head nails (16-40 mm) and type 90 staples (15-40 mm)

**Scope of delivery:** in Systainer; 1000 type SN pan-head nails, length 40mm; 2000 type 90 staples, length 30 mm



Type	Art. no.	Air requirements (l/impact)	Working pressure (bar)	Magazine capacity	Weight (kg)
KNG 40 SYS	D300044	0,7	4 – 7	125	1,4

## Upsetting nail driver



- For securing wooden ceilings, panels, skirting board, decorative strips and manufacturing fences
- Compact design, effortless work for long periods due to low weight
- Contact release for rapid working progress
- With depth regulator for adjusting the insertion depth
- Front panel easy to open without tools in the event of problems
- Non-slip rubber handle reduces vibrations and prevents cold hands
- Rotatable exhaust air guide
- For brad nails type SN, length 16-50 mm

**Scope of delivery:** in Systainer; Protective goggles; 5000 type SN pan-head nails, length 30mm



Type	Art. no.	Air requirements (l/impact)	Working pressure (bar)	Magazine capacity	Weight (kg)
SNG-SK 50 SYS	D300067	1,1	5 – 8	100	1,26

## Type SN pan-head nails

■ NK = galvanised

■ V2A: stainless steel



Type	Art. no.	Wire gauge (mm)	Length (mm)	Packaging unit (piece(s))
SN 113 NK/1000	C520011	0,9x1,2	13	1000
SN 116 NK/1000	C520012	0,9x1,2	16	1000
SN 116 NK/5000	C520002	0,9x1,2	16	5000
SN 120 NK/5000	C520003	0,9x1,2	20	5000
SN 125 NK/1000	C520014	0,9x1,2	25	1000
SN 125 NK/5000	C520004	0,9x1,2	25	5000
SN 130 NK/1000	C520015	0,9x1,2	30	1000
SN 130 NK/5000	C520005	0,9x1,2	30	5000
SN 130 V2A/5000	C521005	0,9x1,2	30	5000
SN 135 NK/5000	C520006	0,9x1,2	35	5000
SN 140 NK/5000	C520008	0,9x1,2	40	5000
SN 150 NK/5000	C520010	0,9x1,2	50	5000

## Pin nailer



- For securing decorative profiles, window beads and ornamentation
- Pin ensures virtually invisible joint, subsequent expansion of holes not necessary
- Extremely compact design, effortless work for long periods due to low weight
- Non-slip rubber handle reduces vibrations and prevents cold hands

- Two-stage trigger prevents injuries caused by tool triggering accidentally
- For pin nails type PN, length 15-25 mm

**Scope of delivery:** in Systainer; Protective goggles



Type	Art. no.	Air requirements (l/impact)	Working pressure (bar)	Magazine capacity	Weight (kg)
PNG-PN 25 SYS	D300068	0,3	4 – 7	102	0,95


## Push pin



■ NK = galvanised

Type	Art. no.	Wire gauge (mm)	Length (mm)	Packaging unit (piece(s))
PN 15-0,6 NK/10000	F440130	0,64	15	10000
PN 18-0,6 NK/10000	F440131	0,64	18	10000
PN 22-0,6 NK/10000	F440132	0,64	22	10000
PN 25-0,6 NK/10000	F440133	0,64	25	10000

## Staples, type 347



■ C = chisel point  
■ NK = galvanised

■ H = resinated

Type	Art. no.	Back width (mm)	Wire gauge (mm)	Length (mm)	Packaging unit (piece(s))	Bulk buying (piece(s))
KL 347/10 CNK/2500	C430003	4,55	0,9x0,7	10	2500	25000
KL 347/16 CNK/2500	C430006	4,55	0,9x0,7	16	2500	25000
KL 347/20 CNK/2500	C430008	4,55	0,9x0,7	20	2500	25000
KL 347/25 CNKH/2500	C430010	4,55	0,9x0,7	25	2500	25000

## T-nail type TN


- NK = galvanised



Type	Art. no.	Wire gauge (mm)	Length (mm)	Packaging unit (piece(s))
TN 22/50 NK/10000	F440014	2,18	50	10000
TN 22/60 NK/10000	F440016	2,18	60	10000
TN 22/63 NK/10000	F440017	2,18	64	10000

## Nail strip type RN

- Round-head nail
- In plastic-bound strips
- BK = bright
- H = resinated



Type	Art. no.	Nail angle (°)	Wire gauge (mm)	Length (mm)	Packaging unit (piece(s))
RN 29/65 BKH/3000	F440021	21	2,9	65	3000
RN 31/70 BKH/3000	F440027	21	3,1	70	3000
RN 31/80 BKH/3000	F440024	21	3,1	80	3000
RN 31/90 BKH/3000	F440025	21	3,1	90	3000
RN 34/100 BKH/2000	F440120	21	3,4	100	2000